




특징(Characteristics)

- 최적설계의 케이스 일체형으로 소음과 진동을 최소화
- 전면 특수 도장 처리로 내식성이 뛰어나고, 외관이 고급스러우며 제품 수명이 연장
- 시공 및 설치가 편리하여 공사시간을 최대한 단축
- AIR조절장치에 의하여 모터에 습기가 부착되는 것을 방지하며, 냉각효과가 우수하여 모터수명을 최대한 연장
- 단 하나의 COVER분리로 A/S와 청소가 손쉽고 빠르게 해결
- 흡입구 설치 시 방향에 관계없이 설치할 수 있으며, 다중 흡입 장치도 가능해 작업성이 탁월함.
- 토출구는 원형으로 설치되어 있으며, 사각토출구도 설치가 가능

용도

- 공기조화용, 일반환기용, 급배기용 시스템.

외형도(Outward Drawing)



규격표(Dimension)

일반MOTOR

고효율MOTOR

모델명	OSB17S	OSB19S	OSB20ST	OSB25ST	OSB28ST	OSB30ST	OSB38FT	OSB38HT	OSB28T	OSB30T	OSB35T	OSB38T	OSB39T
극 수	2P	4P	4P	6P	6P	6P	8P	6P	6P	6P	6P	6P	6P
소비전력	0.1kw	0.2kw	0.4kw	0.4kw	0.75kw	1.5kw	1.5kw	2.2kw	0.75kw	0.75kw	1.5kw	2.2kw	3.7kw
A	300	350	400	515	515	560	725	725	710	750	842	900	1120
B	300	350	400	515	515	560	725	725	515	580	632	750	750
C	300	350	400	515	515	560	655	655	460	530	562	680	680
D	185	220	235	320	320	360	600	600	550	550	600	650	700
E	120	123	165	270	270	328	450	450	400	450	450	500	550
F	185	238	290	400	400	450	600	600	550	550	600	650	700
G	185	238	290	400	400	450	450	450	400	450	450	500	550
H	350	400	450	565	565	630	840	840	765	800	940	1040	1260
I	150	200	350	365	365	405	465	465	260	339	360	486	486
J	410	460	519	635	635	668	780	780	580	650	682	800	800





Characteristics

- Optimized design of case in one type. Minimized the noise and vibration.
- Corrosion resistance with special painting in all surface. Elegant appearance and longer life time.
- Easy set-up and installation. Minimize construction time.
- Prevent motor from humidity with air control device. Excellent cooling effect for longer motor life.
- Easy and fast A/S and cleaning with detach of one cover.
- Can install ventilation opening in any direction. Possible to make multi ventilation system.
- Round type ventilation exit. Possible to make rectangular type as well.

Applications

- Air conditioner system,
Air supply and ventilation system,
General ventilation equipment.

특성 및 사양

Property and Specification

일반MOTOR

형명 Model NO.	상/전압 Phase.Volt	극수 Pols (P)	입력 Input(W)	최대풍량 Air Volume(m ³ /h)	회전수 Revolution(RPM)	중량 Weight(kg)
OSB-17S	220	2	120	614	2,200	15
OSB-19S	220	4	300	1,293	1,700	16
OSB-20S	220	4	400	1,800	1,700	16.8
OSB-25S	220	6	600	3,200	1,100	29
OSB-25T	220/380	6	400	3,200	1,100	29.4
OSB-28S	220	6	750	3,800	1,100	29
OSB-28T	220/380	6	700	3,800	1,100	29.4
OSB-30S	220	6	1,100	5,800	1,100	38.4
OSB-30T	220/380	6	1,100	6,000	1,100	38.4
OSB-38FS	220	8	1,700	8,200	845	62.1
OSB-38FT	220/380	8	1,500	8,200	845	64.8
OSB-38HT	220/380	6	3,200	9,000	1,100	76.8

고효율MOTOR

형명 Model NO.	상/전압 Phase.Volt	극수 Pols (P)	입력 Input(W)	최대풍량 Air Volume(m ³ /h)	회전수 Revolution(RPM)	중량 Weight(kg)
OSB-28T	220/380	6	750	3,500	1,160	50
OSB-30T	220/380	6	750	5,200	1,160	57
OSB-35T	220/380	6	1,500	6,600	1,160	82.8
OSB-38T	220/380	6	2,200	8,200	1,160	125
OSB-39T	220/380	6	3,700	11,000	1,160	153.7

